SAFETY DATA SHEET

1 IDENTIFICATION

Product name :JP-K60

Name of company :Hitachi Industrial Equipment Systems Co., Ltd

Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan

Tel :+81-294-36-8682 Fax :+81-294-36-8975

Recommended use of the chemical

and restrictions on use :Printing Ink for industrial Marking

2 HAZARDS IDENTIFICATION

Physico-chemical endpoints : Flammable liquid Category 2

Acute toxicity - oral : Not available Acute toxicity - dermal : Not available Acute toxicity - inhalation(air) : Not identified Acute toxicity - inhalation (vapors) : Not available Acute toxicity - inhalation (dust, mist) : Not available Skin corrosion/irritation : Not identified Eye damage/irritation : Category 2 Sensitization - respiratory : Not identified Sensitization - skin : Not identified Germ cell mutagenicity : Category 1 Carcinogenicity : Category 2 Toxic to reproduction : Category 1 Effects on or via lactation : Not identified Specific target organ systemic toxicity : (Single exposure)

Category 3 Respiratory tract irritation Category 3 Anesthetizing action

:(Repeated exposure)
Category 1 Liver
Category 1 Lung

Category 2 Nervous system

Aspiration toxicity : Not available

Hazardous to the aquatic environment

-Acute hazard : Not identified -Chronic hazard : Not available

GHS label elements

Hazard symbols:



Signal word: Danger

Hazard statement and precautionary statement:

- Highly flammable liquid and vapor
- · Causes serious eye irritation
- May cause genetic defects
- Suspected of causing cancer
- May damage fertility or the unborn child
- May cause damage to airway irritant, drowsiness or dizziness-single exposure
- Causes damage to liver and lung through prolonged or repeated exposure
- May cause damage to nervous system through prolonged or repeated exposure

Precautionary statements:

 Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

Prevention:

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

Response:

- In case of fire, use dry chemical, CO₂, water splay (fog) or form for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

Storage:

• Store in cool/well-ventilated place. Store locked up.

Call a doctor/physician if exposed or you feel unwell.

Disposal:

Waste must be disposed of according to applicable regulations.

3 Composition/information on ingredients

Substance or mixture; mixture

Composition:

Chemical name	concentration (%)	CAS number
Ethanol	80-90	64-17-5
Carbon black	0.1-1	1333-86-4
2-Propanol	0.1-1	67-63-0

4 First-aid measures

Inhalation:

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the neatest medical facility for examination and treatment by a physician as soon as possible.

Skin contact;

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible, and refer for medical attention.

Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

5 Fire-fighting measures

Suitable extinguishing media;

Use dry chemical, CO₂, water splay (fog) or form.

Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

Unusual fire/explosion hazard:

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

7 Handling and storage

Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

Storage;

Close up the container and keep it in dark cool(0~20°C) place. Keep away from combustible materials and sources of ignition.

8 Exposure controls/personal protection

Exposure guidelines:

ACGIH TLV-TWA (ppm)

Ethanol :1000
Carbon black :3.5mg/cm²
2-Propanol :200

ACGIH STEL(ppm)

Ethanol :No data
Carbon black :None known

2-Propanol :400

9 Physical and chemical properties

Appearance

Physical state :Liquid Color :Black

Odor :Solvent odor Boiling point²⁾ : \geq 79°C

Flash point :14.8°C (closed cup)

Upper/lower flammability or explosive limits²⁾ :Lower 3.3 vol%, Upper 19 vol%

Vapor pressure²⁾ :5.9kPa(20° C) Vapor density (Air=1)²⁾ :1.59(ethanol) Relative density :0.86(20° C)

Solubility (Water)²⁾ :water;infinite(ethanol)

Partition coefficient: n-octanol/water²⁾ :not applicable

Auto-ignition temperature²⁾ :390°C
Decomposition temperature :No data

10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

11 Toxicological information

Acute toxicity:

Ethanol

TDLo(orl,man): 700mg/kg(NTOTDY 8,77,1986) LD50(orl,rat): 9000mg/kg(VCVGK* -, 93, 1984) LC50(ihl,rat): 20000ppm/10h(NPIRI* 1,44,1974)

TCLo(ihl,human): 2500mg/m³/20M(VCVGK* -, 93,1984)

Carbon black None known 2-Propanol

> LD50(orl,rat): 5000mg/kg(VCVGK* -, 97, 1984) LC50(ihl,rat): 72600mg/m³(VCVGK* -, 97, 1984) LC50(ihl,mouse): 53000mg/m³(VCVGK* -, 97, 1984) TDLo(orl,human): 286mg/kg(VCVGK* -, 97, 1984)

Skin corrosion/irritation:

Ethanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -, 189, 1986)

Carbon black None known 2-Propanol

Skin; rabbit; 500mg; Mild(NTIS** AD-A106-944)

Serious eye damage/irritation:

Ethanol

rabbit; 100mg/4S; Moderate(FCTOD7 20,573,1982)

Carbon black None known 2-Propanol

Eye; rabbit; 100mg/24h; Moderate(85JCAE -,191,1986)

Respiratory or skin sensitization:

Ethanol

Not available

Carbon black

None known

2-Propanol

Not available

Germ cell mutagenicity:

Ethanol

DNA damage; S.cerevisiae; 850mmol/L(MUREAV 326,165,1995)

Mutation in microorganisms; S.typhimurium; 11pph(ENVRAL 52, 225, 1990)

Cytogenetic analysis; human; lymphocyte; 2.5pph/24h(MUREAV 537, 117, 2003)

Carbon black

None known

2-Propanol

TDLo(orl,rat): 8mg/kg(female 6-15 D preg)(RTOPDW 23,183,1996)

TCLo(ihl,rat): 3500ppm/7h(female 1-19 D preg)(FCTOD7 26,247,1988)

Carcinogenicity:

Ethanol

TDLo(orl,mouse): 320mg/kg/50W-I(CALEDQ 13,345,1981)

Carbon black
None known
2-Propanol
Not available

Reproductive toxicity:

Ethanol

TDLo(orl,woman): 250mg/kg(37 W preg); Effects on Embryo or Fetus - other effects to embryo(AJOGAH 145,251,1983)

TDLo(orl,rat): 22.5mg/kg(female 11-20 D preg); Specific Developmental Abnormalities - Central Nervous Systems(NETEEC 24, 719, 2002)

Carbon black None known 2-Propanol

TDLo(orl,rat): 8mg/kg(female 6-15 D preg)(RTOPDW 23,183,1996)
TCLo(ihl,rat): 3500ppm/7h(female 1-19 D preg)(FCTOD7 26,247,1988)

STOST-single exposure:

Ethanol

Human ihl, 5000ppm(9,4mg/L), respiratory tract irritation and confusion(ACGIH 2001)

Carbon black

None known

2-Propanol

Not available

STOST-repeated exposure:

Ethanol

Not available

Carbon black

None known

2-Propanol

Not available

Aspiration hazard:

Ethanol

Not available

Carbon black

None known

2-Propanol

Not available

12 Ecological information

Ecotoxicity¹⁾:

Ethanol

daphnids(48h-LC50(g/L)):5463.9(ECETOC TR91 2003)

Carbon black
None known
2-Propanol
guppies(7days-LC50(mg/L)):7060
fathead minnow(1h-LC50(mg/L)):11830

Persistence and degradability:

Ethanol

This material is biodegradable.

Carbon black None known 2-Propanol

This material is biodegradable.

Bioaccumulative potential:

Ethanol

Not available Carbon black None known 2-Propanol Not available

Mobility in soil:

Ethanol

Not available

Carbon black

None known

2-Propanol

Not available

13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burned in an approved incinerator.

Do not dump into sewer, on the ground or into any body of water.

Follow national and local regulations.

14 Transport information

Follow all regulations in your country.

UN Number :1210

UN Proper Shipping Name :Printing ink, flammable Transport hazard class :Class 3(Flammable liquid)

Packing Group : II Environmental hazards :No

15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

16 References

- 1) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan
- 2) International Chemical Safety Cards