# **SAFETY DATA SHEET**

### 1 IDENTIFICATION

Product name :RF-P2

Name of company :Hitachi Industrial Equipment Systems Co., Ltd

Address :1-1, Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan

Tel :+81-294-36-8682 Fax :+81-294-36-8975

Recommended use of the chemical

and restrictions on use :Printing Ink for industrial Marking

### 2 HAZARDS IDENTIFICATION

Physico-chemical endpoints : Flammable liquid Category 2

Acute toxicity - oral : Category 5 Acute toxicity - dermal : Not available Acute toxicity - inhalation(air) : Not identified Acute toxicity - inhalation (vapors) : Not available Acute toxicity - inhalation (dust, mist) : Not available Skin corrosion/irritation : Not identified Eye damage/irritation : Category 2 Sensitization - respiratory : Not available Sensitization - skin : Not available Germ cell mutagenicity : Category 1 Carcinogenicity : Not identified Toxic to reproduction : Category 1 Effects on or via lactation : Not identified Specific target organ systemic toxicity : (Single exposure)

Category 1 Sensory system Category 1 Systemic toxicity

Category 1 Central nervous system

Category 3 Respiratory tract irritation, anesthetizing action

:(Repeated exposure)
Category 1 Liver

Category 1 Sensory system

Category 1 Central nervous system

Category 2 Nervous system

Aspiration toxicity : Not identified

Hazardous to the aquatic environment

-Acute hazard : Not identified -Chronic hazard : Not identified

#### **GHS** label elements

Hazard symbols:



Signal word: Danger

### Hazard statement and precautionary statement:

- Highly flammable liquid and vapor
- May be harmful if swallowed
- Causes serious eye irritation
- May cause genetic defects
- May damage fertility or the unborn child
- Causes damage to Sensory system, systemic toxicity or central nervous system-single exposure
- May cause damage to airway irritant, drowsiness or dizziness-single exposure
- Causes damage to liver, sensory system or central nervous system through prolonged or repeated exposure
- May cause damage to nervous system through prolonged or repeated exposure

#### **Precautionary statements:**

 Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

#### Prevention:

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- · Wash hands thoroughly after handling.

### Response:

- In case of fire, use dry chemical, CO<sub>2</sub>, water splay (fog) or form for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

#### Storage:

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

## Disposal:

Waste must be disposed of according to applicable regulations.

# 3 Composition/information on ingredients

#### Substance or mixture; mixture

Composition:

Chemical nameconcentration (%)CAS numberMethanol50-6067-56-1Ethanol1-1064-17-5

#### 4 First-aid measures

#### Inhalation:

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the neatest medical facility for examination and treatment by a physician as soon as possible.

#### Skin contact:

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

#### Eye contact;

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible, and refer for medical attention.

### Ingestion;

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medical attention.

# 5 Fire-fighting measures

#### Suitable extinguishing media;

Use dry chemical, CO<sub>2</sub>, water splay (fog) or form.

### Fire fighting procedures;

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

### Unusual fire/explosion hazard;

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

### Special protective equipment and precautions for fire fighters;

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

#### 6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

# 7 Handling and storage

### Handling;

Use only in the well-ventilated areas.

Make available in the work area emergency shower and eyes wash.

Avoid contact with skin or eyes.

# Storage;

Close up the container and keep it in dark cool(0~20°C) place. Keep away from combustible materials and sources of ignition.

# 8 Exposure controls/personal protection

### **Exposure guidelines:**

ACGIH TLV-TWA (ppm)

Methanol :200(skin) Ethanol :1000

ACGIH STEL(ppm)

Methanol :250(skin) Ethanol :No data

## 9 Physical and chemical properties

**Appearance** 

Physical state :Liquid
Color :Clear
Odor :Solvent odor
Boiling point<sup>2)</sup> :65-100°C

Flash point :19.0°C (closed cup)

Upper/lower flammability or explosive limits<sup>2)</sup> :Lower 6.0 vol%, Upper 36 vol%

Vapor pressure<sup>2)</sup> :12.7kPa (20°C) Vapor density (Air=1)<sup>2)</sup> :2.1 (methanol) Relative density :0.89(20°C)

Solubility (Water)<sup>2)</sup> :water;infinite(methanol)

Partition coefficient: n-octanol/water<sup>2)</sup> :Log Pow=-0.82/-0.66(methanol)

Auto-ignition temperature<sup>2)</sup> :423°C
Decomposition temperature :No data

## 10 Stability and reactivity

Stability: The product is stable.

Conditions and materials to avoid: Not available

Hazardous decomposition products: These products are carbon oxides

# 11 Toxicological information

#### Acute toxicity:

Methanol

LD50(orl,rat): 5628mg/kg(GTPZAB 19(11),27,1975) LC50(ihl,rat): 64000ppm/4h(NPIRI\* 1,74,1974) TDLo(orl,man): 9450µL/kg(AJEMEN 16,538,1998) TCLo(ihl,human): 300ppm(NPIRI\* 1,74,1974)

Ethanol

TDLo(orl,man): 700mg/kg(NTOTDY 8,77,1986) LD50(orl,rat): 9000mg/kg(VCVGK\* -, 93, 1984) LC50(ihl,rat): 20000ppm/10h(NPIRI\* 1,44,1974)

TCLo(ihl,human): 2500mg/m³/20M(VCVGK\* -, 93,1984)

#### Skin corrosion/irritation:

Methanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -,187,1986)

Ethanol

Skin; rabbit; 20mg/24h; Moderate(85JCAE -, 189, 1986)

#### Serious eye damage/irritation:

Methanol

Eye; rabbit; 100mg/24h; Moderate(85JCAE -,187,1986)

Ethano

rabbit; 100mg/4S; Moderate(FCTOD7 20,573,1982)

#### Respiratory or skin sensitization:

Methanol

Allergic dermatitis; human, skin(PATTY 4th,1994)

No skin sensitization ;Magnusson-Kligman maximization test, guinea pig(EHC 196,1997: DFGOT vol. 16,2001)

Ethanol

Not available

# Germ cell mutagenicity:

Methanol

Mutation in microorganisms; mouse; lymphocyte; 7900mg/L(ENMUDM 7(Suppl 3),10,1985)

thanol

DNA damage; S.cerevisiae; 850mmol/L(MUREAV 326,165,1995)

Mutation in microorganisms; S.typhimurium; 11pph(ENVRAL 52, 225, 1990) Cytogenetic analysis; human; lymphocyte; 2.5pph/24h(MUREAV 537, 117, 2003)

### Carcinogenicity:

Methanol

Not available

Ethanol

TDLo(orl,mouse): 320mg/kg/50W-I(CALEDQ 13,345,1981)

### Reproductive toxicity:

Methanol

TCLo(ihl,rat): 10000ppm/7h(7-15 D preg)(FAATDF 5,727,1985) TDLo(orl,rat): 5200µL/kg(10 D preg)(REPTED 11,503,1997)

Ethanol

TDLo(orl,woman): 250mg/kg(37 W preg); Effects on Embryo or Fetus - other effects to embryo(AJOGAH 145,251,1983)

TDLo(orl,rat): 22.5mg/kg(female 11-20 D preg); Specific Developmental Abnormalities - Central Nervous Systems(NETEEC 24, 719, 2002)

### STOST-single exposure:

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001), The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994), Anesthesia, rat, mouse and rhesus monkey(EHC 196,1997; PATTY 4th,1994)

Ethanol

Human ihl, 5000ppm(9,4mg/L), respiratory tract irritation and confusion(ACGIH 2001)

### STOST-repeated exposure:

Methanol

The restraint of central nervous system and damage of the visual organ, human, oral or ihl(EHC 196,1997; ACGIH, 7th,2001; DFGOT vol.16, 2001), The respiratory tract irritation, rat,(EHC 196,1997; PATTY 4th,1994), Anesthesia, rat, mouse and rhesus monkey(EHC 196,1997; PATTY 4th,1994) Ethanol

Not available

### **Aspiration hazard:**

Methanol Not available Ethanol Not available

### 12 Ecological information

# Ecotoxicity<sup>1)</sup>:

Methanol

Not available

Ethano

daphnids(48h-LC50(g/L)):5463.9(ECETOC TR91 2003)

#### Persistence and degradability:

Methanol

This material is biodegradable.

Ethanol

This material is biodegradable.

#### Bioaccumulative potential:

Methanol Not available Ethanol Not available

### Mobility in soil:

Methanol Not available Ethanol Not available

# 13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burned in an approved incinerator.

Do not dump into sewer, on the ground or into any body of water.

Follow national and local regulations.

# **14 Transport information**

Follow all regulations in your country.

UN Number :1210

UN Proper Shipping Name :Printing ink, flammable Transport hazard class :Class 3(Flammable liquid)

Packing Group : II Environmental hazards :No

# 15 Regulatory information

Follow all regulations in your country.

Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

### 16 References

- 1) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan
- 2) International Chemical Safety Cards